Blackhawk
123 Gaither Drive
Mt. Laurel, NJ 08054-1701
www.blackhawk-dsp.com
+1-856-234-2629

Blackhawk is a registered trademark of EWA Technologies, Inc.

QUICK START GUIDE

Blackhawk™ XDS560 Trace Product (XDS560T)

REQUIREMENTS

- PC or Notebook computer with at least one free USB v1.1 or v2.0 port.
- Windows® 2000 or XP Operating System.
- Qualified XDS560-Class Emulator
- Texas Instruments CCStudio Version 3.3† or later.
- CD-ROM Drive.
- Target board with supported TI DSP

Contents

Emulator Driver CD ROM

Quick Start Guide, Warranty and Registration cards

Trace Pod

60 pin to 14 pin JTAG pin-converter

+12V Universal Trace Pod Power Supply

60 pin to 60 pin JTAG pin saver

Trace Pod AC Power Cord Set for US, UK, EU with Ferrites for +12v Power Supply Power Cord

This product requires Code Composer Studio v3.3† or later.

Where To Go Next

Please refer to the Quick Start Guide included with this XDS560 Trace Cable hardware that matches your XDS560-class emulator from the list below.

- Blackhawk USB560m JTAG Emulator - USB560T-QS-02
- Blackhawk LAN560 JTAG Emulator - LAN560T-QS-01
- Blackhawk PCI560 JTAG Emulator - PCI560T-QS-01

† You must have CCStudio v3.3 or later installed (*not included with this product*). Using an earlier version will not work and is not supported.